




ISOLATORS & FUSED SWITCHES

ROTARY ISOLATORS

METAL ISOLATOR SWITCH 4P 32A

- 4pole 32A for isolating incoming supplies.
- 20mm knockouts top, bottom & side.
- Padlockable in OFF position (not included).
- BS EN 60947-3 compliant.


Part No.	Description	Dimensions (mm)		
		H	W	D
M324P	32A (AC22A) 4pole	110	145	55



METAL ROTARY ISOLATORS 4P (IP65)

- Robust steel enclosure.
- Generous cabling space.
- Door interlock to prevent access to live conductors.
- Lockable in OFF position with 3 padlocks (not included).
- AC21 for switching of resistive loads.
- AC22A for switching of mixed resistive & inductive loads.
- Rated short circuit making capacity: 3000A.
- Rated withstand current: 12In 1second.
- BS EN 60947-3 compliant.

Part No.	Description	Dimensions (mm)		
		H	W	D
S323P	32A (AC21) / 25A (AC22A)	250	250	175
S633P	63A (AC21) / 40A (AC22A)	250	250	175
S1003P	100A (AC21) / 180A (AC22A)	250	250	175
S1253P	125A (AC21) / 100A (AC22A)	250	250	175



INSULATED HI-VIS ISOLATORS 4P (IP56)

- 4pole enclosed isolators (IP56).
- High visibility.
- Supplied c/w 4x 25mm entries & 2x 20mm adaptors for easy installation.
- Padlockable in ON or OFF position (not included).
- AC22A for switching of mixed resistive & inductive loads.
- BS EN 60947-3 compliant.

Part No.	Description	Dimensions (mm)		
		H	W	D
ISO-20	20A (AC22A) 4pole	175	85	88
ISO-35	35A (AC22A) 4pole	175	85	88
ISO-63	63A (AC22A) 4pole	175	85	88

