





**MINIATURE 5V OUTPUT HIGH TEMPERATURE PRESSURE TRANSDUCER WITH INTEGRATED TEMPERATURE SENSOR**  
**ETL/T-HT-375 (M) SERIES**

- Combined Pressure and Temperature Measurement Capability
- 5 VDC Output
- 365°F Temperature Capability
- Hybrid Microelectronic Regulator-Amplifier
- Flush Diaphragm
- Robust Construction
- Patented Leadless Technology **VIS**<sup>®</sup>
- All Welded Construction
- Designed For Automotive Applications
- Secondary Containment On Absolute And Sealed Gage Units
- 3/8-24 UNJF or M10 X 1 Thread



The ETL/T-HT-375 is a miniature threaded pressure transducer/platinum RTD combination. The pressure transducer utilizes a patented silicon on silicon design. The platinum RTD protrudes beside the diaphragm to sense media temperature. The pressure and temperature devices are designed to operate independently. All wetted parts of the transducer are compatible with most industrial and automotive fluids. Part performance not guaranteed if used in water.



INPUT	Pressure Range	0.7 10	1.0 15	1.7 25	3.5 50	7 100	17 250	35 500	70 1000	170 BAR 2500 PSI	
	Operational Mode	Absolute		Absolute, Sealed Gage							
	Over Pressure	2 Times Rated Pressure to 1000 PSI (70 BAR) 1.5 Times Rated Pressure Above 1000 PSI to a Max. of 3000 PSI (207 BAR)									
	Burst Pressure	3 Times Rated Pressure to a Max. of 3000 PSI (207 BAR)									
	Pressure Media	Most Conductive Liquids and Gases - Please Consult Factory (All Media May Not Be Suitable With O-Ring Supplied)									
	Maximum Electrical Current	25 mA									
	Rated Electrical Excitation	8 - 16 VDC					15 - 32 VDC				
	RTD Excitation	1mA (2mA Max.)									
OUTPUT	Full Scale Reading	5 VDC ± 75mV (3 Wire System Single Ended Output)									
	Residual Unbalance	0.5V ± 75mV									
	Output Impedance	200 Ohms (Typ.)									
	RTD	1000 Ohms Platinum, DIN EN 60751 Tables, Class A (65% Response Time 3 Seconds Max.) in Liquid									
	Bandwidth (-3dB)	DC to 5 kHz									
	Combined Non-Linearity, Hysteresis and Repeatability	± 0.1% BFSL (Typ.), ± 0.5% BFSL (Max.)									
ENVIRONMENTAL	Resolution	Infinitesimal									
	Acceleration Sensitivity % FS/g Perpendicular	1.0x10 <sup>-3</sup>	6.5x10 <sup>-4</sup>	5.0x10 <sup>-4</sup>	3.0x10 <sup>-4</sup>	1.5x10 <sup>-4</sup>	1.0x10 <sup>-4</sup>	6.0x10 <sup>-5</sup>	4.0x10 <sup>-5</sup>	2.5x10 <sup>-5</sup>	
	Insulation Resistance	100 Megohm Min. @ 50 VDC									
	Operating Temperature Range	-4°F to +365°F (-20°C to +185°C)									
	Compensated Temperature Range	+32°F to +350°F (0°C to +175°C)									
	Thermal Zero Shift	± 1% FS/100°F (Typ.)									
	Thermal Sensitivity Shift	± 1% /100°F (Typ.)									
	Linear Vibration	20g Peak, Sine 10 to 2000 Hz									
	Mechanical Shock	20g Half Sine Wave 11 msec. Duration									
	PHYSICAL	Electrical Connection	5 Conductor 26 AWG Shielded Cable 40" (1 Meter) Long								
Weight		20 Grams Excluding Cable									
Pressure Sensing Principle		Fully Active Four Arm Wheatstone Bridge Dielectrically Isolated Silicon on Silicon Patented Leadless Technology									
Mounting Torque		50 Inch-Pounds (Max.) 6Nm									

Note: Custom pressure ranges, accuracies, mechanical configurations and RTD resistance available. Dimensions are in inches. Dimensions in parenthesis are in millimeters. All dimensions nominal. (C) Continuous development and refinement of our products may result in specification changes without notice. Copyright © 2014 Kulite Semiconductor Products, Inc. All Rights Reserved. Kulite miniature pressure transducers are intended for use in test and research and development programs and are not necessarily designed to be used in production applications. For products designed to be used in production programs, please consult the factory.