

## TYPE GBL

### Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- Lay-in feature

### Benefits

- Suitable for use with copper or aluminum conductors
- Provides low contact resistance
- Provides ease of installation




Fig. 1




Fig. 2




Fig. 3

| Catalog Number | Figure Number | Ground Wire Range | Bolt Size | Dimensions |       |       |        |       |       |         | Hex Size |
|----------------|---------------|-------------------|-----------|------------|-------|-------|--------|-------|-------|---------|----------|
|                |               |                   |           | C          | D     | E     | F      | G     | H     | T       |          |
| * GBL-4        | 1             | 4-14              | 10        | 7/32       | 5/8   | 31/64 | 1-3/32 | 13/64 | 25/64 | 51/64   | Slot     |
| + ‡ GBL-4SS    | 2             | 4-14              | 10        | 7/32       | 5/8   | 31/64 | 1-3/32 | 13/64 | 25/64 | 51/64   | Slot     |
| GBL-1/0        | 2             | 1/0-14            | 1/4       | 9/32       | 51/64 | 27/32 | 1-5/8  | 7/16  | 5/8   | 1-5/32  | Slot     |
| GBL-250        | 3             | 250kcmil-6        | 1/4       | 9/32       | 31/64 | 1     | 2-3/16 | 29/64 | 7/8   | 1-23/32 | 7/32     |

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

UL File E34440

\* UL 467 and UL 486A/B Listed

+ UL 467 Listed

‡ GBL-4SS is UL2703 Listed UL E354420 Vol. 2

+ Supplied with stainless steel hardware. Meets ASTM B117-09 and is resistant to outdoor salt spray

DE-OX® oxide inhibitor is recommended for all aluminum terminations

Optional MH Series mounting hardware kits available, consult ILSCO