

CALRAD


30 series - connectors

Technical drawings and specifications are available for these connectors. Please ask your Calrad sales representative for details.




30-395
Open Circuit.

30-396
Closed Circuit.
2-Conductor
1/4" Phone Jack.
3/8" bushing.
Mounts in .355" hole.



30-397

1/4" Phone Jack.
Open Circuit
3-Conductor.
3/8" bushing.
Mounts in .355" hole.



30-398

1/4" Phone Jack.
3-Circuit,
2 Closed.
3/8" bushing.
Mounts in .355" hole.



30-399

1/4" Phone Jack.
3-Circuit,
3 Closed.
3/8" bushing.
Mounts in .355" hole.



30-400

3 Circuit 1/4"
Stereo Jack.
.35" x .29" bushing.
.36" hole size, will
work with standard
.375" hole.




30-411

Open Circuit 1/4"
Monaural Jack.
.36" hole size, will
work with standard
.375" hole.




30-412

Closed Circuit 1/4"
Monaural Jack.
.35" x .29" bushing.
.36" hole size, will work
with standard .375" hole.



30-385

Stereo 1/4"
Phone Jack. With
normally closed
and normally
open circuits.



30-394

Stereo 1/4"
Phone Jack. One
Closed Circuit.
.355" hole size.



30-366

PC Mount. RCA
Jack. Closed
Circuit.



30-424

RCA Panel Jack.
Locking nut fits on
front of panel.
Shallow mounting
depth. Mounts in
3/8" hole. Bushing
length .26"



30-410-1/2

RCA to RCA feedthru jack for
audio/video panels. Mounts in
1/2" hole. Bushing length
.29" Overall length 1.35"
Available with different color
inserts: red, green, blue, white,
yellow. **Specify color when
ordering.**



30-410G-BK
30-410G-RD
30-410G-YL
30-410G-W

Same as 30-410 with gold
plating. Red, black, yellow,
white inserts. Bushing length
.29" Overall length 1.36"



30-410-3/8

RCA to RCA feedthru jack for
audio/video panels. Mounts in
3/8" hole. Bushing length is
.39" / overall length is 1.14".
Available with different color
inserts: red, green, blue, white,
yellow, and black. **Specify
size and color when
ordering.**



30-295
30-295G

3.5mm female to
female bulk head feed-
thru jack. Mounts in
3/8" hole. Overall
length 1.43". Available
in gold or nickel plated.



30-428-BK
30-428-RD
30-428-W
30-428-YL

Nickel plated RCA phono
jack with hex nut and solder
lug. Single hole mount.
1/4" hole. Black or red
insert. Bushing length .25"



30-428G-BK
30-428G-RD
30-428G-W
30-428G-YL

Same as 30-428 with gold
plating. Black, white, red,
or yellow insert. Bushing
length .25".



30-425-BK
30-425-RD

RCA-type mini
phono jack with hex
nut grip, hex nut and
solder lug. Single hole
mount. 1/4" hole.
9mm hex base.
Bushing length .27".



30-300-BK
30-300-RD
30-300-WH
30-300-YL

RCA chassis mount jack. Gold
plated with teflon insulator mount.
Fits 3/16" hole. Knurled outside
with black & red band.
Bushing length .43"



30-368-BK
30-368-RD
30-368-WH
30-368G-BK
30-368G-RD
30-368G-WH

PC mount RCA jack
with black or red insert.
Gold version.



30-367

Gold Right angle, PC
mount RCA Jack.
Bushing length .1"
30-367-NK
Nickel version.
30-367-T
Threaded (nickel).
30-367G-T
Threaded (gold).
Available with red,
white, yellow, green,
and blue inserts.
Specify color when
ordering.



30-364

3.5 mm mono
miniature printed
circuit jack.
Normally closed
circuit.



30-365

2.5 mm mono
miniature printed
circuit jack.
Closed circuit.



30-422

3.5 mm miniature
closed circuit mono
jack mounts in 1/4"
hole in panels up to
1/8" thick. Nickel
plated. Bushing
length .17".

CALRAD

30 series - connectors

Technical drawings and specifications are available for these connectors. Please ask your Calrad sales representative for details.



NEW Item

30-477

3.5mm mini stereo jack. Black PVC plastic construction, perfect for mounting in tight places. Measures only .33"L x .35"W x .23"H with solderable leads. Bushing length .135". Mounts in a .25" hole.



30-478

Mono 2.5 mm sub-mini closed or open circuit jack, mounts in panels up to 1/16" thick. Comes with nut and washer. Bushing length .149".



30-491

Mini 3 circuit stereo jack. 3.5 mm open circuit, PC-type.



30-493A

Mini 3.5mm stereo jack. Panel mount. Mounts in 1/4" hole. Bushing length .165".



30-494A

Mini 2.5mm stereo jack. Panel mount. Mounts in 1/4" hole. Bushing length .16".



30-494

2.5 mm stereo, sub-miniature jack. Mounts in 1/4" hole. Bushing length .13".



NEW Item

30-297

Locking inline 3.5mm female stereo jack. Black chrome body. Mates to 30-296 locking plug.



NEW Item

30-700A

4 conductor 3.5mm chassis mount jack. Tip, ring 1, ring 2, sleeve. Mounts in .28" hole.



30-413

Slim 1/4" stereo inline phone jack. Mates w/30-401. .3" cable opening.



30-420

Same as 30-413 but with metal housing and strain relief. .26" cable opening.



30-415 (black) 30-415-RD (red)

Slim inline 1/4" mono phone jack. Mates w/30-402. Black or red. 1/2" dia. x 1 1/16" long. .3" cable opening.



30-415M

Same as 30-415 with metal housing. .31" cable opening.



30-414

Metal 3.5 mm mono inline female jack (2-conductor). .16" cable opening.



30-487

Mini inline 3.5 mm stereo jack, plastic handle w/strain relief. .19" cable opening.

30-487A

Mono version.

30-487G

Gold version.



30-492

Mini 3 circuit shielded stereo jack. 3.5 mm inline, black metal finish. .14" cable opening.



30-417

3.5mm inline stereo jack. Metal housing with strain relief. .2" cable opening.



NEW Item

30-319F

Professional quality 3.5mm stereo inline jack with strain relief. .26" cable opening. Mates with Calrad male 3.5mm connector 30-319.



NEW Item

30-705

Inline female 4 conductor 3.5mm jack. Tip, ring 1, ring 2, sleeve. Plastic shell with strain relief. Mates to 30-700A, 30-701, and 30-702 plugs.



30-479

2.5mm inline stereo jack. .13" cable opening.



30-390

Shielded RCA phono plug, gold plated. .2" cable opening.



30-391

Shielded RCA inline phone jack, gold plated. .2" cable opening.



30-387

Gold plated, heavy duty RCA plug for use on cable up to RG59 coax. Spring strain relief. .28" cable opening.

30-387-NK

Nickel version.



30-308

Professional quality RCA plug with gold solid pin and nickel barrel. .24" cable opening.



30-427

Shielded RCA phone plug. Nickel plated. With strain relief. .2" cable opening.

CALRAD

30 series - connectors

Technical drawings and specifications are available for these connectors. Please ask your Calrad sales representative for details.



30-429
Shielded, nickel plated RCA-type inline jack w/cable clamp. 3/8" dia., 1" long. .21" cable opening.



30-350
Gold plated RCA plug with color coded red band. .21" cable opening.



30-351
Gold plated RCA inline jack with color coded red band. .21" cable opening.



30-352
Gold plated RCA plug with color coded white band. .21" cable opening.



30-353
Gold plated RCA inline jack with color coded white band. .21" cable opening.



30-307
Professional quality gold RCA plug with solid center pin. .25" cable opening.



30-309
Gold inline female RCA connector with finger grip body, finished in nickel. Accepts cables up to .24" in diameter.



NEW Colors
30-303-BK
30-303-RD
30-303-YL
30-303-WH
RCA plug for 5-7mm diameter wire. Black, red, or yellow band. Gold plated. .29" cable opening.



NEW Item
30-302
Gold plated RCA plug with teflon insulator for 6-8mm cable. Specify black, red, white or yellow band. Gold plated. .35" cable opening.



NEW Item
30-289
Gold plated 75 ohm RCA plug for 6mm cable. Specify plain or colored bands when ordering. Bands: red, green, black, blue, white, and yellow. .22" cable opening.



NEW Item
30-290
Gold plated 75 ohm RCA plug for 8mm cable. Specify plain or colored bands when ordering. Bands: red, green, black, blue, white, and yellow. .32" cable opening.



NEW Item
30-291
Gold plated 75 ohm RCA plug for RG-174, 2.8mm cable. Specify plain or colored bands when ordering. Bands: red, green, black, blue, white, and yellow. .12" cable opening.



NEW Item
30-292
Gold plated 75 ohm RCA plug for 4mm cable. Specify plain or colored bands when ordering. Bands: red, green, black, blue, white, and yellow. .16" cable opening.



30-607-BK
30-607-RD
Locking RCA plug for up to 8 mm wire. With black or red band. Teflon insulator. .35" cable opening.



NEW Item
30-6075-BK
30-6075-RD
Solderless locking RCA plug with screw terminals for up to 8 mm wire. With black or red band. Teflon insulator. .35" cable opening.



30-305 L=.95"
Right angle RCA plug, heavy gold plating, teflon insulator, 8 mm cable, short version.
30-306 L=1.3"
Long version.
.37" cable opening for both.



NEW Item
30-299-WH
30-299-RD
Gold plated high grade home theater series. Locking RCA connector for 12-14mm cable.



NEW Item
30-301-RD
30-301-W
Gold plated high grade home theater series. Locking RCA connector for 10-12mm cable.



NEW Item
30-354 RG59
30-354 RG6
75ohm gold RCA connector. Recessed barrel provides a low profile when inserted into a female jack. Solder center pin at base of connector, fold shield over PVC, a 2 piece twist type compression fitting is used to secure the shield to the connector.



30-389
RCA male solderless screw terminals, cable clamp and rubber boot. .24" cable opening.



30-446 red
30-447 black
RCA phono plugs w/ screw on plastic barrel & cable clamp. Specify color. .18" cable opening.



30-448 red
30-449 black
RCA Phone Jack with cable clamp and plastic barrel. Specify Color. .18" cable opening.



30-426
Insulated RCA pin plugs. 4 per Pkg. - 2 red and 2 black. .12" cable opening.



NEW Colors
30-430
Insulated RCA plugs, built-in cable clamps. Easy slip-on plastic covers. Pkg'd 10 per bag. Two each of red, blue, black, white, green, and yellow. Available in Bulk. .19" cable opening.

CALRAD

30 series - connectors

Technical drawings and specifications are available for these connectors. Please ask your Calrad sales representative for details.



30-384
Right angle RCA plug.
Solderless connector
with cable clamp.
.19" cable opening.



30-486
Molded RCA
termination plug,
gold plated.



30-402-BK
30-402-RD
1/4" mono phone
plug w/solder
terminals & cable
clamp. Black or red.
.28" cable opening.



30-401-BK
30-401-RD
3-circuit 1/4" stereo
plug w/ cable clamp.
Std. type fits open or
closed phone jacks.
Black & red.
.28" cable opening.



30-419
1/4" mono plug.
Large barrel heavy
duty type. Accepts
oversize gauge wire.
.43" cable opening.
30-419G
Gold version.



30-405
1/4" mono plug. with thick
walled barrel. 8mm hole for
large gauge wire.
30-405A
Stereo version.
.32" cable opening for both.



30-620
1/4" mono solder type plug
with strain relief. Black, blue,
red, yellow, and green -
specify color.

30-621
Stereo version. .15" to .3"
cable opening for both



30-622-BK
30-622-BU
30-622-GN
30-622-OR
30-622-RD
30-622-YL
Colored strain reliefs for
30-620 and 30-621.



30-316
Professional quality
1/4" mono plug
with strain relief.
.25" cable
opening.



30-317
Professional quality
1/4" stereo plug
with strain relief.
.25" cable
opening.



30-404 &
30-404G gold
1/4" Mono phone
plug with strain relief.
.28" cable opening.



30-418 &
30-418G gold
1/4" Stereo phone
plug with strain relief.
.27" cable opening.



30-536
1/4" Mono phone
plug w/screw
terminals and strain
relief spring.
.25" cable opening.



30-537
1/4" Stereo phone
plug w/screw
terminals and strain
relief spring.
.25" cable opening.



30-406
Flat right-angle,
shielded 1/4"
mono phone plug in
metal case. Solder
terminals.
.29" cable opening.



30-408A
Flat right-angle,
shielded 1/4" 3-
circuit stereo phone
plug in metal case.
Solder terminals.
.29" cable opening.



30-407
1/4" mono right
angle plug, black
bakelite. Solder
terminals w/cable
clamp.
.28" cable opening.



30-409
1/4" stereo right
angle stereo plug,
black bakelite.
.28" cable opening.



30-416-BK
30-416-RD
3.5 mm mono plug
w/solder terminals &
cable clamp.
Specify color.
.18" cable opening.



30-421
3.5 mm shielded
mono plug in metal
housing with solder
terminals and spring
strain relief.
.18" cable opening.



30-376
3.5 mm right angle
mono phone plug.
.15" cable opening.

30-386
Stereo version.



30-376-2.5 (mono)
30-386-2.5 (stereo)
2.5mm mono and
stereo right angle mini
plugs. Solder terminals
with snap-on black
PVC plastic body.
.15" cable opening.



30-423A
2.5 mm sub-mini
plug w/plastic grip,
2 cond. Improved
solder points. 7/16"
plug length.
.15" cable opening.



30-485
2.5 mm stereo plug with
strain relief and metal
housing.
30-485A
Mono version.
.13" cable opening for both.

CALRAD

30 series - connectors

Technical drawings and specifications are available for these connectors. Please ask your Calrad sales representative for details.



NEW Item
30-488 stereo
30-488G gold

3.5 mm dia., mini stereo plug with plastic handle and molded strain relief. .16" cable opening.

30-488A
Mono version.



30-489

3.5 mm dia., stereo plug with plastic handle. .21" cable opening.



30-484

3.5 mm stereo plug, strain relief spring, solder type, and metal housing. .19" cable opening.



30-490

3.5 mm, shielded mini stereo plug, black metal finish with strain relief. .14" cable opening.



30-318

Professional quality 3.5mm mono plug with strain relief. .25" cable opening.



30-319

Professional quality 3.5mm stereo plug with strain relief. .26" cable opening.



NEW Item

30-701

4 conductor 3.5mm plug. Tip, ring 1, ring 2, sleeve. Plastic housing with strain relief. Cable opening .14"



NEW Item

30-702

4 conductor 3.5mm right angle plug. Tip, ring 1, ring 2, sleeve. Cable opening .14"



NEW Item

30-296

Gold plated locking inline 3.5mm male stereo plug with black chrome body. Mates to 30-297 and 30-493A jacks.



30-370

2.1 mm pin, PC mount coax power jack, switched normally closed circuit.



30-370-2.5

2.5 mm pin, PC mount coax power jack, switched circuit.



30-371

Coax power jack, standard chassis mount, 2.1mm pin. Switched circuit. 17mm mount center.



NEW Item

30-624-2.1
30-624-2.5

Chassis mount locking DC power coax jack. Mates with 30-623 plug. Mounts in panels up to .07". Available in 2.1mm or 2.5mm center pin I.D.



NEW Item

30-623-2.1
30-623-2.5

Locking DC power coax plug. Mates with 30-624 jack. Turning clockwise secures the plug to the jack. Available in 2.1mm or 2.5mm I.D. Cable opening .18"



NEW Item

30-616-2.1
30-616-2.5

Locking DC power coax jack with N/C switch on sleeve side of the connector. Insert 30-617 plug and twist clockwise to lock.



NEW Item

30-617-2.1
30-617-2.5

Locking DC power coax plug 5.5 O.D., 9.5mm long. Insert into 30-616 jack and twist clockwise to lock. Cable opening .14"



30-355

Right angle coax power plug. 1.3mm I.D., 3.5mm O.D. with solder terminals. .22" x .12" cable opening.



30-356

Right angle coax power plug. 2.1mm I.D., 5.5mm O.D. with solder terminals. .22" x .12" cable opening.



30-357

Right angle coax power plug. 2.5mm I.D., 5.5mm O.D. with solder terminals. .22" x .12" cable opening.



NEW Item

30-337

Coax AC/DC power plug 2.35mm O.D., .7mm I.D. .17" cable opening with strain relief.



30-336

Coaxial power plug. 1.0mm I.D. 3.8mm O.D. .17" cable opening.



30-372

Coax power plug. 1.3 mm I.D., 3.5 mm O.D., 9.5 mm long. .15" cable opening.
30-372-P
With strain relief. .16" cable opening.



30-373

Coax power plug. 2.1 mm I.D., 5.5 mm O.D., 9.5 mm long. .15" cable opening.
30-373-P
With strain relief. .16" cable opening. Molded strain relief.



30-373-HG

High grade version of 30-373.

CALRAD

30 series - connectors

Technical drawings and specifications are available for these connectors. Please ask your Calrad sales representative for details.



30-374

Coax power plug. 2.5 mm I.D., 5.5 mm O.D., 9.5 mm long. .15" cable opening.

30-374-P

With strain relief. .16" cable opening.



30-635

Coax AC/DC power plug 4.75mm O.D., 1.7mm I.D.

.17" cable opening with strain relief.



30-375

DC coax power plug. 3 mm I.D., 6.3 mm O.D., 9.5 mm long.

With strain relief. .20" cable opening.



30-348

Power plug converter 3.5mm plug to 2.1mm jack.



30-349

Power plug converter 3.5mm plug to 2.5mm jack.



30-333

2.1 mm coax inline female connector.

30-334

2.5mm version. .15" cable opening.



30-340

Coax power plug converter. 1.3 mm plug to 2.1 mm jack.

30-341

2.5 mm jack version.



30-343

Coax power plug converter. 2.5 mm plug to 2.1 mm jack.

30-344

2.5 mm jack version.



30-346

Coax power plug converter. 3.0 mm plug to 2.1 mm jack.

30-347

2.5 mm jack version.



3.5 mm mono mini-jack to DC power plug.

30-360

1.3 mm coax plug I.D.

30-361

2.1 mm coax plug I.D.

30-362

2.5 mm coax plug I.D.



30-363

3.5 mm mini-jack to DC power plug. 3.0 mm coax plug I.D.



30-377

2.1mm I.D. x 5.5mm O.D., chassis mount coax power jack. For 7/16" dia. hole in panels up to 3/16" thick.



30-378

2.5mm I.D. x 5.5mm O.D., chassis mount coax power jack. For 7/16" dia. hole in panels up to 3/16" thick.



30-379

3.0mm I.D. x 6.3mm O.D., chassis mount coax power jack. For 7/16" dia. hole in panels up to 3/16" thick.



30-310

2.1mm I.D. x 5.5mm O.D. Chassis mount coax power jack. Insulated housing mounts in 5/16" hole. N/C switch.




30-311

2.5mm I.D. x 5.5mm O.D. Chassis mount coax power jack. Insulated housing. Mounts in 5/16" hole. N/C switch.



30-314

2.1mm I.D. x 5.5mm O.D. Chassis mount coax power jack. Plastic housing. Mounts in 1/2" dia. hole. N/C switch.



30-315

2.5mm I.D. x 5.5mm O.D. Chassis mount coax power jack. Plastic housing. Mounts in 1/2" dia. hole. N/C switch.



30-442 Black 30-443 Red

Insulated banana plug, 1" molded bakelite handle, .2" cable opening.



30-442G Black 30-443G Red

Gold versions of 30-442 and 30-443. .2" cable opening.



30-600-BK 30-600-RD

Banana plug, gold plated solderless with female banana tap. Black or red. .22" cable opening.



30-602-BK 30-602-RD

Banana plug, solderless with gold plating, screw adjustment, black or red band. .15" cable opening.



30-603

Locking banana plug, can be locked down in jack, solderless, gold plated. .34" cable opening.



30-605-BK 30-605-RD

Solder type banana plug for large cable. Gold plated with black or red bands. Up to 8 awg wire. .25" cable opening.

CALRAD

30 series - connectors

Technical drawings and specifications are available for these connectors. Please ask your Calrad sales representative for details.



30-604-RD
30-604-BK
Dual gold banana plugs. For up to 8 gauge wire. Black or red. .15" cable opening. 0.75" centers.



30-440 red
30-441 black
Dual banana plug, gold plated. Black or red. .24" cable opening. 0.75" centers.



30-440-NK (red)
30-441-NK (black)
Dual banana plug, nickel plated. Black or red. .24" cable opening. 0.75" centers.



30-438
BNC female to dual standard banana plugs. 0.75" centers.



30-439
BNC male to dual binding post, for wire or standard banana plugs. 0.75" centers.



30-460
BNC male to dual standard banana plugs. 0.75" centers.



30-461
BNC female to dual binding post, for wire or standard banana plugs. 0.75" centers.



30-444 black
30-445 red
Insulated banana jack. Supplied with soldering lug and nuts.



30-610 (red+black)
Speaker pin plug, gold plated with P.V.C. cover, crimp. 30-610-RD, Red or 30-610-BK, black. Comes 1-red, 1-blk.



30-606-BK
30-606-RD
Solderless speaker pin plug. Accepts up to 8 awg wire. With red or black band.



NEW Item

30-609-RD
30-609-WH
Speaker terminals with solder/solderless speaker pin plug and white/red color ID and. Accepts 8-18 awg. cable. Gold plated with black chrome finish.



5-way binding posts. Plastic insulation. Has .1875" keyed threaded mounting shaft. Will mount in panels up to .25" thick. Colors shown below.
90-799Black
90-800Red



30-613-BK
30-613-RD
Spade terminal, gold plated crimp on connector, with P.V.C. cover, black or red. .15" to .3" cable opening.



30-615-BK
30-615-RD
Power spade terminal, heavy duty gold plated, screw type adjustment with black or red band. .25" cable opening.



90-808
Spade lugs. Color-coded 5 red, 5 lack per package. Rear of lug will accommodate Calrad 90-809 subminiature plug.



30-369
Right angle, 2-pin male speaker plug. .23" x .13" cable opening.



30-392
2-pin inline male speaker plug. .23" x .11" cable opening.



30-393
2-pin inline female speaker plug. .26" x .17" cable opening.



Shielded inline mini male DIN plugs. Rated at 12 Vdc, 2A max. Accepts up to .20" O.D.
30-3203-pin
30-3224-pin
30-3245-pin
30-3266-pin
30-3287-pin
30-3308-pin



30-505
Pro quality SVHS 4-pin connect for up to 5.7mm cable. Metal housing with gold pins and gold strain relief. .27" cable opening.



NEW Item

30-505-6
Pro quality SVHS 6-pin connect for up to 5.7mm cable. Metal housing with gold pins and gold strain relief. .27" cable opening.



NEW Item

30-608
Pro quality SVHS 4-pin connect for 8mm cable. Metal housing with gold pins and gold strain relief. .31" cable opening.



NEW Item

30-322J-4
30-322J-6
30-322J-8
Inline female SVHS connector. Solder type inline female connector with strain relief. Shielded body with plastic cover. Available in 4, 6, or 8 pin.



NEW Item

30-618
SVHS inline female jack. Solder type connector. Accepts 5-7mm cable. Black chrome body with gold plated connector.

30-619
For use with 8mm cable.

CALRAD

30 series - connectors

Technical drawings and specifications are available for these connectors. Please ask your Calrad sales representative for details.



NEW Item


30-618-6
6 pin SVHS inline female jack. Solder type connector. Accepts 5-7mm cable. Black chrome body with gold plated connector.

30-618-8
8 pin connector.



NEW Item

30-505-RA
Right angle SVHS connector. gold plated connectoe accepts up to 8mm cable and provides a low profile cable termination. the front can pivot 180°. Cable reduction boots are available for 5mm cables and smaller.



Female mini DIN connector printed circuit mount socket.

30-3213-pin
30-3234-pin
30-3255-pin
30-3276-pin
30-3297-pin
30-3318-pin



30-506
4-pin SVHS chassis mount jack with screws for mounting.



30-507
SVHS 4-pin chassis mount jack. Mounts in 9/16" hole. Bushing length .167".

30-507-6
SVHS 6-pin.



.26" cable opening.

Male DIN plugs

30-435.....3-pin inline 180°
30-436.....5-pin inline 180°
30-499.....6-pin inline 240°
30-495.....7-pin inline 270°
30-497...8-pin inline 270°, "U" pattern
30-503...8-pin inline 360°, circular pattern



.26" cable opening.

Female DIN plugs

30-433.....5-pin inline 180°
30-500.....6-pin inline 240°
30-496.....7-pin inline 270°
30-498...8-pin inline 270°, "U" pattern
30-504...8-pin inline 360°, circular pattern
All above have plastic strain relief.



30-437
5-pin male DIN plug and 5-pin inline female DIN jack. .26" cable opening for both. Plastic strain relief




30-501
6-pin (240°) right angle male DIN plug.

30-502
5-pin (180°) version. .18" cable opening and plastic strain relief for both.




30-508
5-pin (180°) DIN female socket, chassis mount.


30-509
6-pin (240°) version.




30-542
5-pin (180°) PC chassis mount DIN jack.



30-543
6-pin (240°) PC chassis mount DIN jack.



30-544
7-pin (270°) PC chassis mount DIN jack.



30-545
8-pin (270°) "U" pattern, PC chassis mount DIN jack.



30-546
8-pin (360°) circular pattern PC chassis mount DIN jack.



30-457
4-prong male interlocking inline DIN connector.

30-458
5-prong version. .27" cable opening for both.



30-480
4-prong female interlocking inline DIN connector. .27" cable opening.

30-481
5-prong version.



30-482 - 4-pin
30-483 - 5-pin
Interlocking DIN-type chassis jacks. Accepts locking ring-type DIN plugs such as Calrad 30-457, 4-pin & 30-458, 5-pin plugs.



30-459
Y-type 4-pin mic connector, nickel plated, strain relief clamp. "Y" hole pattern. Size: 1 1/2" OVL x 5/8" dia.



30-451
3 conductor inline jack. .25" cable opening.

30-451-M
3 conductor male plug.



30-452
3 conductor male chassis plug. .62" hole size.



30-453
4 conductor inline jack. .25" cable opening.

30-453M
4 conductor male plug.



30-454
4 conductor male chassis plug. .62" hole size.



NEW Item

30-518
5-pin microphone inline jack. .25" cable opening.

30-518-M
5 conductor male plug.

CALRAD

30 series - connectors

Technical drawings and specifications are available for these connectors. Please ask your Calrad sales representative for details.



30-519
5-pin chassis
mount
microphone plug.
.62" hole size.



NEW Item

30-455
6 conductor inline
jack. .25" cable
opening.

30-455-M
6 conductor
male plug.



30-456
6 conductor male
chassis plug.
.62" hole size.



NEW Item

30-510
7 conductor inline
jack. .25" cable
opening.

30-510-M
7 conductor male
plug.



30-511
7-pin male
chassis plug.
.62" hole size.



NEW Item

30-512
8-pin inline jack.
.25" cable opening.

30-512-M
8 conductor
male plug.



30-513
8-pin male
chassis plug.
.62" hole size.



30-467
PL259 Coax
chassis connector
(box-type).



30-468
PL259 Coax
chassis connector
(bullet-type).
5/8" hole size.



30-475
Coax adaptor
plug. Adapts PL
259 type to
3.5 mm jack.



30-469
Coax universal jack
adaptor. Adapts PL
259 to Motorola-type
auto antenna jack or
RCA-type phone jack.



30-470
Coax
right angle
adaptor SO-239
to PL-259.



30-471
Coax "T"
connector adapts
2 females to
one male.



30-472
Coax double
female
connector.



30-473
Coax cable
adaptor for RG58U.

30-474
Coax cable
adaptor for RG59U.



30-465
Coax cable
connector plug.



30-530
10-pin male
inline video
camera plug.
.38" cable
opening.



30-531
10-pin female
inline video
camera plug.
.38" cable
opening.



30-532
10-pin female
chassis mount
video camera
jack.
.64" hole size.



silver or black

30-520-SL
30-520-BK
XLR 3-pin male
inline plug.
.25" cable
opening.



silver or black

30-521-SL
30-521-BK
XLR 3-pin female
inline plug.
.25" cable
opening.



silver or black

30-529-SL
30-529-BK
XLR 3-pin male plug,
twist-on strain relief.
.15" to .3" cable
opening. No tools
required for assembly
or disassembly. 4
piece construction.
Internal compression
style cable strain relief.



silver or black

30-528-SL
30-528-BK
XLR 3-pin female plug,
twist-on strain relief.
.15" to .3" cable
opening. No tools
required for assembly or
disassembly. 4 piece
construction. Internal
compression style cable
strain relief.



silver or black

30-526-SL
30-526-BK
XLR 3-pin female
right angle plug.
.17" cable
opening.

CALRAD

30 series - connectors

Technical drawings and specifications are available for these connectors. Please ask your Calrad sales representative for details.



silver or black

30-527-SL
30-527-BK
XLR 3-pin male
right angle plug.
.17" cable
opening.



30-534
4-pin XLR male plug.
Color is silver.
30-535
4-pin XLR inline female
plug. Color is silver.
.25" cable opening
for both.



30-539-BK
30-539-SL
5-pin XLR male plug.
Color is silver or black.
30-540-BK
30-540-SL
5-pin XLR inline female plug.
Color is silver or black.
.25" cable opening.



NEW Item

30-630-BK-3
30-630-BK-4
30-630-BK-5
Black inline male XLR plug,
3, 4, or 5-pin. .15" to .3"
cable opening. No tools
required for assembly or
disassembly. 4 piece
construction. Internal
compression style cable
strain relief.



NEW Item

30-630-SL-3
30-630-SL-4
30-630-SL-5
Silver inline male XLR plug, 3, 4,
or 5-pin. .15" to .3" cable
opening. No tools required for
assembly or disassembly. 4 piece
construction. Internal compression
style cable strain relief.



NEW Item

30-631-BK-3
30-631-BK-4
30-631-BK-5
Black inline female XLR plug, 3, 4,
or 5-pin. .15" to .3" cable
opening. No tools required for
assembly or disassembly. 4 piece
construction. Internal compression
style cable strain relief.



NEW Item

30-631-SL-3
30-631-SL-4
30-631-SL-5
Silver inline female XLR plug, 3,
4, or 5-pin. .15" to .3" cable
opening. No tools required for
assembly or disassembly. 4 piece
construction. Internal compression
style cable strain relief.



NEW Item

30-640-3
30-640-4
30-640-5
30-640-6
Inline male mini XLR plug.
Available in 3, 4, and 5
pin. Also available with
short boot. Cable opening
.13"-.17"



NEW Item

30-641-3
30-641-4
30-641-5
30-641-6
Inline female mini XLR
jack. Available in 3, 4,
and 5 pin. Also available
with short boot. Cable
opening .13"-.17"



NEW Item

30-641M-3
30-641M-4
30-641M-5
30-641M-6
Metal inline female mini
XLR jack. Available in 3,
4, and 5 pin. Also
available with short boot.
Cable opening .13"-.17"



30-525
XLR 3 pin female
to female
coupler.



30-524
XLR 3 pin male
to male coupler.



silver or black

30-522-SL
30-522-BK
XLR 3-pin male
chassis plug.
.75" hole size.



30-522-SL-4
4-pin male XLR
chassis jack
mounts in .75"
hole size.



NEW Item

30-522-SL-5
5-pin male XLR
chassis jack
mounts in .75"
hole size.



NEW Item

silver or black

30-523-SL
30-523-BK
XLR 3-pin female
chassis jack.
.75" hole size.



NEW Item

30-523-SL-4
4-pin female XLR
chassis jack
mounts in .75"
hole size.



NEW Item

30-523-SL-5
5-pin female XLR
chassis jack
mounts in .75"
hole size.



30-515
Plastic XLR 3-pin
male chassis
plug.
.76" hole size.



30-516
Plastic XLR 3-pin
female chassis
jack.
.86" hole size.



NEW Item

30-642-3
30-642-4
30-642-5
30-642-6
Chassis mount mini
XLR male. Mounts in
.43" "D" hole. Nickel
plated body. Available
in 3, 4, 5, and 6 pin.



NEW Item

30-643-3,
-4,-5,-6
Chassis mount female
XLR. Mounts in
15.20mm, .60 hole.
Nickel plated body.
Mates with Calrad
30-640 connectors.
Available in 3, 4, or
5 pin.



NEW Item

30-517
Isolated plastic female
XLR with protective
cover. 3-pin female
XLR mounts in 15/16"
hole and requires a
special cut out in order
to mount.



30-595
XLR single female
jack on steel plate.
30-596
XLR double female
jack on steel plate.

CALRAD

30 series - connectors

Technical drawings and specifications are available for these connectors. Please ask your Calrad sales representative for details.



NEW Item

30-590

Female XLR desktop mount in black, used for quick release style gooseneck mics. Removable solder type female XLR. Mounts with 3 screws included. Base dia. 1.75", height 2".



30-432

Standard mic connector, male or inline female. Fits std. 5/8" .27 chassis connectors. Knurled collar screws to convert to male. .2" cable opening



30-434

Mic connector. Bright chrome plated. .21" cable opening.



30-380

Chassis mount antenna jack. Female receptacle. .4" hole size.



30-381

Antenna-type plug. To fit Calrad 30-380.



30-382

In-line solderless Motorola type plug. .26" cable opening.



30-383

Motorola type antenna in-line twist on jack, no soldering. .3" cable opening.




"D"

solder type connector plugs.
30-550 . . . 9-way
30-551 . . . 15-way
30-552 . . . 25-way



"D"

solder type connector sockets.
30-560 . . . 9-way
30-561 . . . 15-way
30-562 . . . 25-way



Hoods

30-550-PH..... 9-pin plastic
 30-550-MH .. 9-pin metalized plastic
 30-550-M..... 9-pin metal
 30-551-PH..... 15-pin plastic
 30-551-MH 15-pin metalized plastic
 30-551-M..... 15-pin D conn. metal
 30-552-PH..... 25-pin plastic
 30-552-MH 25-pin metalized plastic
 30-552-M..... 25-pin metal



NEW Item

30-553M

DB9, DB15HD metal housing for 10-11mm cable, with hardware. 2-piece construction, for use with DB9, DB15 type connectors.

30-553M-G
Gold version.



NEW Item


30-553M-RA
Right angle version of 30-553M.
30-553M-RA-G
Gold plated right angle hood and hardware.



NEW Item

30-551-HD

DB-15 high density male plug used for computer monitor applications, graphic workstations, computer and data related applications. Numbered pins. Gold plated terminals.



NEW Item

30-561-HD

DB-15 high density female jack used for computer monitor applications, graphic workstations, computer and data related applications. Numbered pins. Gold plated terminals.




30-580

9-pin "D" connector plug to 9-pin "D" connector plug mini version.



30-582

9-pin "D" connector socket to 9-pin "D" connector socket mini version.



NEW Item

30-588

15-pin male to male gender changer. High density "D" connector plugs for inline or panel mounting.



NEW Item

30-587

15-pin female to female gender changer. High density "D" connector sockets for inline or panel mounting.



NEW Item

30-584-M

15 pin gender changer. Male- male.



NEW Item

30-584-F

15 pin gender changer. Female-female.



30-575

25-way "D" connector plug to 25-way "D" connector plug mini version.



30-577

25-way "D" connector socket to 25-way "D" connector socket mini version.



30-581

Male 9-pin "D" connector plug to 9-pin "D" connector plug.



30-583

Female 9-pin "D" connector socket to 9-pin "D" connector socket.

CALRAD

Calrad - connectors

Technical drawings and specifications are available for these connectors. Please ask your Calrad sales representative for details.



30-576
25-way "D"
connector plug to
25-way "D"
connector plug.



30-578
25-way "D"
connector socket
to 25-way "D"
connector socket.



30-579
25-pin to 25-pin
modem adapter.



30-585
25-pin male plug
to 9-pin "D"
connector socket.



30-586
25-pin socket to
9-pin plug.



30-597
15 pin high density "D" cutout
single gang stainless steel wall
plate with hardware. For male or
female connectors. Works with
Calrad part #s 30-580, 30-582,
30-587, 30-588.



30-598
15 pin wide "D" cutout single
gang stainless steel wall plate
with hardware. For male or
female connectors. Works
with Calrad part #s
30-584M, 30-584F.



30-599
25 pin "D" cutout single
gang stainless steel wall
plate with hardware. For
male or female connectors.
Works with Calrad part #s
30-575, 30-577.



30-591
For use with Calrad
"D" sub connectors.
.2" length. 4-40
threads. Package of
6 pieces.



**Rubber Boots
for Connectors**
Used to color
code audio and
video connectors.
30-289-BK..... Black
30-289-BU..... Blue
30-289-GN..... Green
30-289-RD..... Red
30-289-WH..... White
30-289-YL..... Yellow



30-554
Solder type DB-9,
9 pin male with
metal hood and
hardware.
Accepts cable up
to 11mm, .433".



30-555
Solder type DB-9,
9 pin female with
metal hood and
hardware.
Accepts cable up
to 11mm, .433".



30-556
Solder type HD-
15, 15 pin male
with metal hood
and hardware.
Accepts cable up
to 11mm, .433".



30-557
Solder type HD-
15, 15 pin female
with metal hood
and hardware.
Accepts cable up
to 11mm, .433".



Calrad Electronics
produces custom
cables. Fax your
drawings & specs to
our 24 hour fax line.
323-465-3504