

SPD 2 CONDUCTOR MALE

- Range taking permits inventories to be kept to a minimum.
- Re-usable
- UL486A/B and UL 467 Listed
- For grounding of steel structures, fence post and tapping cables from bus bar.
- For copper to copper connections.
- SPDL Double conductor - Long Stud
- SPDS Double conductor - Short Stud



1

Item ID	Conductor Range Maximum	Conductor Range Minimum	Conductor Range Diameter	Bolt/Stud Size	Standard Package Quantity	NAED/UPC Number
SPDL-0	8 AWG - 8 Sol. (10 mm2)	12 AWG (4 mm2) - 12 Sol. (4 mm2)	.146" - .080"	1/4"-20 x 1"	50	78366923300
SPDL-1	7 AWG (10 mm2) - 6 Sol. (10 mm2)	10 AWG (6 mm2) - 10 Sol. (6 mm2)	.170" - .102"	1/4"-20 x 1"	50	78366923301
SPDL-2	5 AWG (16 mm2) - 4 Sol. (16 mm2)	10 AWG (6 mm2) - 10 Sol. (6 mm2)	.217" - .102"	5/16"-18 x 1"	50	78366923302
SPDL-3	3 AWG (25 mm2) - 2 Sol. (35 mm2)	10 AWG (6 mm2) - 10 Sol. (6 mm2)	.271" - .102"	3/8"-16 x 1-1/8"	50	78366923303
SPDL-4	1 AWG (35 mm2) - 2 Sol. (35 mm2)	8 AWG (6 mm2) - 8 Sol. (10 mm2)	.332" - .128"	3/8"-16 x 1-1/8"	50	78366923304
SPDL-5	1/0 AWG (50 mm2) - 2 Sol. (35 mm2)	2 AWG (35 mm2)	.385" - .258"	1/2"-13 x 1-1/4"	25	78366923305
SPDL-6	2/0 AWG (70 mm2) - 2 Sol. (35 mm2)	2 AWG (35 mm2)	.443" - .258"	1/2"-13 x 1-1/4"	25	78366923306
SPDL-8	4/0 AWG (95 mm2)	1 AWG (35 mm2)	.570" - .289"	5/8"-11 x 1-1/2"	25	78366923307
SPDL-9	350 kcmil (150 mm2)	1/0 AWG (70 mm2)	.715" - .373"	5/8"-11 x 1-1/2"	10	78366923308
SPDL-10	500 kcmil (240 mm2)	3/0 AWG (95 mm2)	.840" - .464"	3/4"-10 x 1-3/4"	10	78366923309
SPDS-0	8 AWG - 8 Sol. (10 mm2)	12 AWG (4 mm2) - 12 Sol. (4 mm2)	.146" - .080"	1/4"-20 x 1/2"	50	78366923310
SPDS-1	7 AWG (10 mm2) - 6 Sol. (10 mm2)	10 AWG (6 mm2) - 10 Sol. (6 mm2)	.170" - .102"	1/4"-20 x 1/2"	50	78366923311
SPDS-2	5 AWG (16 mm2) - 4 Sol. (16 mm2)	10 AWG (6 mm2) - 10 Sol. (6 mm2)	.217" - .102"	5/16"-18 x 5/8"	50	78366923312
SPDS-3	3 AWG (25 mm2) - 2 Sol. (35 mm2)	10 AWG (6 mm2) - 10 Sol. (6 mm2)	.271" - .102"	3/8"-16 x 5/8"	50	78366923313
SPDS-4	1 AWG (35 mm2) - 2 Sol. (35 mm2)	8 AWG (6 mm2) - 8 Sol. (10 mm2)	.332" - .128"	3/8"-16 x 5/8"	50	78366923314
SPDS-5	1/0 AWG (50 mm2) - 2 Sol. (35 mm2)	2 AWG (35 mm2)	.385" - .258"	1/2"-13 x 3/4"	25	78366923315
SPDS-6	2/0 AWG (70 mm2) - 2 Sol. (35 mm2)	2 AWG (35 mm2)	.443" - .258"	1/2"-13 x 3/4"	25	78366923316
SPDS-8	4/0 AWG (95 mm2)	1 AWG (35 mm2)	.570" - .289"	5/8"-11 x 1"	25	78366923317
SPDS-9	350 kcmil (150 mm2)	1/0 AWG (70 mm2)	.715" - .373"	5/8"-11 x 1"	10	78366923318
SPDS-10	500 kcmil (240 mm2)	3/0 AWG (95 mm2)	.840" - .464"	3/4"-10 x 1-1/4"	10	78366923319

RETURN