DEGSON ELECTRONICS CO., LTD.

Product Specification



DG78-···-05AH

Approval		
Electrical		
Standard	**UL**	**IEC**
Rated voltage	600V	750V
Rated current	40A	41A
Wire range	18-10AWG	6.0mm²
With standing voltage	AC3000V/1Min	
Insulation Resistance	500MΩ/DC500V	
Mechanical		
Max. Torque Value	1.2N.m 10.6Lb.in	
Ambient temperature	-40℃~+105℃	
Dimensions		
Pitch	13.0mm(.512″)	
Poles	2P-18P	
Material		
Housing	PA66+23%GF,UL94V-0	
Terminal	Brass,1.0t Tin plated	
Screws	Steel,M4 Ni plated	



HOW TO ORDER :



Poles	2	3	4	5	6	7	8	9	10	11	12	13	14	15
L(mm)	29.30	42.30	55.30	68.30	81.30	94.30	107.30	120.30	133.30	146.30	159.30	172.30	185.30	198.30
S(mm)	13.00	26.00	39.00	52.00	65.00	78.00	91.00	104.00	117.00	130.00	143.00	156.00	169.00	182.00

Poles	16	17	18	19	20	21	22	23	24	25	26	27	28	
L(mm)	211.30	224.30	237.30	250.30	263.30	276.30	289.30	302.30	315.30	328.30	341.30			
S(mm)	195.00	208.00	221.00	234.00	247.00	260.00	273.00	286.00	299.00	312.00	325.00			

mm
(INCH)

THIRDANGLE PROJECTION

DEGSON ELECTRONICS CO., LTD.

NAME

DG78H-A